

## Wasag applicator

Applicator for the preparation of uniform films of coating materials, adhesives and similar products on plane substrates for testing purposes.

### Handling

Only use on solid substrates, such as test panels, test charts, ...

Place the applicator with the desired gap height on the substrate to be coated

Pour the product to be tested in front of the applicator in drawing direction and apply with uniform speed (about 25mm/s)

Afterwards clean the applicator with a solvent



### Technical specifications

Version	Film width	Gap height
ZWA 2121.80	80 mm	2 on request from 15 µm to 2 000 µm (in steps of five) (0,6 mil - 78,7 mil)
ZWA 2121.120	120 mm	
ZWA 21210.180	180 mm	
ZWA 2121.230	230 mm	
ZWA 2121.S1	on request: from 20 mm to 500 mm	
ZWA 2121.S	on request: from 20 mm to 500 mm	with different gap heights on side (stairs) from 15 µm to 2 000 µm (in steps of five)

### Material

stainless steel

### Features

The coating cannot get under the guide shoes and thereby adulterate the applied film thickness

### Standard extent of delivery

- 1 applicator
- 1 certificate of manufacturer
- 1 carrying case

### Options

- Automatic film applicator coater
- Precision-vacuum plates
- Test charts
- Calibration and certification (incl. certificate)