

Rotawash colorfastness tester

To determine color fastness to washing or dry cleaning to ISO, BSI AATCC and SDC standards. Fitted with programmer allowing automatic selection of all AATCC, ISO and other test methods with individual parameters displayed, select one of last 3 tests, select user defined program, COM port for updates. Now features a newly improved color touch control panel. Includes drain pump, inching facility and lid interlock.

Washpots or accessories not included:

M228B - Capacity 8 washpots x 550ml or 8 x 1200ml

M228C - Capacity 12 washpots x 550ml or 12 x 1200ml

M228P1 - 550ml Washpot with lid and seal

M228P2 - 1200ml Washpot with lid and seal

Physical specifications

Dimensions

660 mm x 600 mm x 950 mm (W x D x H)

Weight

75 kg

Standards

AATCC 28, AATCC 61, ATCC 86, AATCC 132

BS 1006

ISO 105-C01, ISO 105-C02, ISO 105-C03, ISO 105-C04, ISO 105-C06, ISO 105-C07, ISO 105-C08, ISO 105-C09, ISO 105-D01, ISO 105-E03, ISO 105-E12

M&S C4A, M&S C5, M&S P3B, M&S C10A, M&S C11, M&S C26, M&S C37, M&S C49A, M&S P137

NEXT 2, NEXT 2A, NEXT 3, NEXT 3A, NEXT 5

IWSTM 7, IWSTM 115, IWSTM 177, IWSTM 193, IWSTM 199, IWSTM 240, IWSTM 241

