









LINEAR ABRASER



Measure abrasion resistance and other material properties of finished products of any size or shape - flat, concave or convex.

The Linear Abraser uses a free-floating head to follow the contours of every sample, permitting testing of finished products. With virtually no limit on sample size or shape, the Linear Abraser is ideal for testing consumer products, automotive components, painted parts, printedgraphics, optical products, rubber, leather, textiles, and for use in testing laboratories.

Versatile testing with a single, rugged, durable machine.

With adjustable stroke length, speed, load, and a wide selection of Taber attachments, the Linear Abraser allows you to customize test parameters to your exact needs. Optional attachments can be used to perform scratch, coin scrape, Crockmeter, rub, pencil hardness scratch, paperclip mar, magnetic stripe abrasion, wire insulation scrape, chemical rub, plus custom testing.



The Linear Abraser abrades with a Wearaser®. The size and shape of a pencil eraser, the Wearaser uses the same highquality Taber abrasive media found in our world-famous wheels so you're assured of consistent test results.



Linear Abraser includes:




- Wearaser Collet and Spline Shaft (350 grams)
- 250 gram Weight Discs (3 ea.)
- CS-10 Wearasers (pkg. 10)
- H-18 Wearasers (pkg. 5)
- Power Cords (115V & 230V)
- Hex L-Key Tool
- Wearaser Depth Gauge Tool
- S-14 Refacing Strips (pkg. 50)
- Hand Brush

Optional Accessories (sold separately):

- Wide selection of abradants:
- Calibrase® CS-8, CS-10F, CS-10, CS-17
- Calibrade® H-10, H-18, H-22, H-38
- T-Slot Universal Table
- Auxiliary weight discs (10, 20, 50, 75, 100, 150, 250 gram)
- Light weight spline kit
- Jumbo Wearaser Collet
- Universal Attachment
- Scotchbrite® Abrasive Pad Kit
- Brass Brush Holder
- Wire/Cable Scrape Abrasion Kit
- Magnetic Stripe Abrasion Kit

Standard features

- Eleven stroke lengths (0.2" to 4.0")
- Variable stroke speed from 2 75 cycles per minute
- Preset stroke speed buttons for 2, 15, 25, 30, 40, 60 cycles per minute
- Variable load from 350 2100 grams with optional weight discs
- Stainless Steel Wearaser Collet for use with vitrified or resilient Wearsers
- Laser alignment guide
- Programmable up to 999,999 cycles
- 115V/230V switchable
- CE Label



RYCOBEL GROUP Nijverheidslaan 47 8540 Deerlijk, België T +32 (0)56 78 21 70 F+32 (0)56 77 30 40 E info@rycobel.com www.rycobel.com







